



Read your safety manual that came with your chain saw.

If you are going to help clear tree and wood debris, you should wear at least:

- A helmet system
- Cotton or leather gloves
- Chain saw protective chaps or chain saw protective pants (UL Listed)
- A pair of chain saw protective work boots with steel toes

Read your owner's manual concerning kickback. To reduce the risk of kickback injury:

- Use a reduced kickback bar, low kickback chain and chain brake
- Avoid contact between the bar tip and any object
- Hold the chain saw firmly with both hands
- Do not over-reach
- Do not cut above shoulder height
- Check the chain brake frequently
- Follow sharpening and maintenance instructions for the chain saw

Make sure that your chain saw has these features, and that the features are working:

- Chain brake (manual or inertia)
- Chain catcher
- Working safety throttle switch
- Working on/off switch
- Spark arrester

Fill a gas-powered chain saw when the engine is cool.

- If the saw is out of gas, let it cool 30 minutes before refueling.
- Do not smoke when refueling the saw! Use a chain saw outdoors only.

Look out for hazards!

- Broken or hanging branches, attached vines, or a dead tree that is leaning
- If you have to cut a dead tree, be very careful! The top could break off and kill you.
- If the tree is broken and under pressure, make sure you know which way the pressure is going. If you're not sure, make small cuts to release some of the pressure before cutting up the section.
- Be careful of young trees that other trees have fallen on. They act like spring poles and may propel the chain saw back into your leg. (Many professional loggers have been hurt in this manner.)

Felling a dangerous broken tree should be left to a professional cutter.

- A downed tree may weigh several tons and can easily injure or kill an unaware chain saw operator. More injuries occur during clean up after a hurricane than during the storm.

Carry the chain saw with the engine off.

When bucking up (cutting) a downed tree:

- Place a plastic wedge into the cut to keep your chain saw from binding up. They are available at any chain saw dealer and sometimes come packaged with the saw.

Never cut when tired or alone.

- Most woodcutting accidents occur late in the afternoon when most people are pushing to finish up for the day.
- Always work with a partner but never around children or pets.

Use a chain saw from the ground level only, not on a ladder or in a tree.

When felling a tree, keep everyone at least "two tree lengths away."

You should have a preplanned escape route.

- It should be at a 45° angle from the projected direction of a falling tree. Make sure there is nothing that could trip or stop you from making a quick retreat.

When picking up heavy wood debris, get several helpers.

- Bend your knees and lift with your legs, not your back.
- A 24-inch log may weigh over 100 pounds.

Cleaning up tree damage after a storm is a very demanding job. If you follow these basic tips you can avoid preventable injuries.

- This information was provided courtesy of Gränsfors Bruks, Inc., a manufacturer/supplier of logging safety apparel and accessories, of Summerville, S.C., and is used with permission. This information has also been reviewed for technical accuracy by the U.S. Consumer Product Safety Commission.